

CONDUCTOR STRINGING EQUIPMENT

Four Drum Pullers

3,000 lbs. and 4,000 lbs. Puller for Conductor Installation



MODELS DP-30-4H and DP-40-4H

These four drum pullers with four separate pulling drums and ropes allow for the simultaneous or individual pulling in of three conductors and an earthwire.

STANDARD FEATURES

- Proven hydraulic pulling system with mechanical clutch for each drum.
- Water-cooled diesel engine.
- Infinitely variable linespeed and linepull control.
- Spring applied / hydraulic pressure released holding brake.
- Four heavy duty pulling drums, each with capacity for 10,000 ft. of 5/8" diameter or 14,000 ft. of 1/2" diameter rope.
- Free-wheeling drum disconnect for high speed rope payout
- Hydraulic bronze overspin brake on each drum.
- Four hydraulic boom type levelwinds controlled from operator's console.
- Central operator's position for maximum safety and visibility with engraved console panel.
- Tandem axle trailer with leaf spring suspension.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

03-17-2014

TSE International, Inc.
5301 Shreveport-Blanchard Highway
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com



CONDUCTOR STRINGING EQUIPMENT

Four Drum Pullers

3,000 lbs. and 4,000 lbs. Puller for Conductor Installation

| MODEL | DP30-4H | DP40-4H |
|--|--|---|
| PERFORMANCE: Continuous Torque Rating Intermittent Torque Rating Continuous Linepull Rating Infinitely Variable Speed | (Single Drum) 72,000 in.-lbs. 80,000 in.-lbs. 3,000 lbs. Full Drum 0 to 4.0 mph Full Drum | (Single Drum) 92,000 in.-lbs. 100,000 in.-lbs. 4,000 lbs. Full Drum 0 to 4.0 mph Full Drum |
| DRUM CAPACITY: Drum Outside Diameter Drum Width Drum Core Diameter Drum Rope Capacity Synthetic Rope | 48 in. 31 in. 18 in. 10,000 ft. of 5/8 inch Diameter or 14,000 ft. of 1/2 inch Diameter | 48 in. 31 in. 18 in. 10,000 ft. of 5/8 inch Diameter |
| DRIVE SYSTEM: Engine Hydraulic Drive Drive Train Brake Drum Engagement Free Wheeling Disconnect Bronze Overspin Brakes | 49 H.P. Water-Cooled Diesel Closed Loop Hydrostatic Spring Applied/Hydraulic Released Mechanical Clutch on Each Drum Standard on Each Drum 24 inch Diameter on Each Drum | 74 H.P. Water-Cooled Diesel Closed Loop Hydrostatic Spring Applied/Hydraulic Released Mechanical Clutch on Each Drum Standard on Each Drum 24 inch Diameter on Each Drum |
| UNIT DIMENSIONS: Length Width Height Weight (including rope) | 19 ft. 6 in. 8 ft. 0 in. 8 ft. 0 in. 18,340 lbs. | 19 ft. 6 in. 8 ft. 0 in. 8 ft. 6 in. 19,000 lbs. |
| TRAILER: Axles Trailer Brakes Tires GAWR GVWR Tow Hitch Front Jack Rear Jacks Trailer Lighting Fenders | 18,000 lbs. Tandem with Leaf Spring Electric (4) LT 215/75R17.5 "H" 18,000 lbs. 20,000 lbs. 3 Inch Pintle Eye with 4 Height Adjustments One Hydraulic Two, Drop Leg Manual Screw Type D.O.T. 4 Light System, 7 Wire Connector Diamond Plate with Mudflaps | |
| GENERAL FEATURES: | | |
| <ul style="list-style-type: none"> • 19 Gallon Fuel Reservoir with Level Gauge • 30 Gallon Hydraulic Reservoir with Level and Temperature Gauges • Operator's Protective Screen and Seat • Elevated Operator's Position for Maximum Safety and Visibility • Steel Lockable Battery Box • Two Hydraulic Boom Type Levelwinds • Unit Sandblasted, Primed and Painted with two coats of enamel finish paint | | |
| OPERATOR'S CONTROLS: | | |
| <ul style="list-style-type: none"> • Direction Control Lever with Infinite Speed Adjustment and Anti-Payout Stop • Adjustable Pull / Tension Control with Bypass if Preset Tension is Reached • Holding Brake Apply / Release Control • Hydraulic System Pressure Gauge • Engine Controls: Keyed Ignition, Throttle Control, Choke Control • Levelwind Speed and Direction Controls (not included with Optional Automatic Leadscrew Levelwinds) • Permanently Engraved Operator's Control Panel | | |

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

TSE International, Inc.
5301 Shreveport-Blanchard Highway
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com