

CONDUCTOR STRINGING EQUIPMENT *SLCT 22 Cable Trailer*



REEL HANDLING

- * Maximum Reel diameter 108"
- * Minimum Reel diameter 60"
- * Maximum Reel Width 68"
- * Minimum Reel Width 38"
- * Maximum Reel Weight 22,000 lbs.
- * 5" Spindle Stubs

DIMENSIONS (Less Reel)

- * Length 188"
- * Width 96"
- * Height 120"
- * Weight 14,000 lbs. Approx.
- * GVWR 37,400 lbs.

OPTIONS

- * Hydraulic reel shaft rewind.
- * Reel Tensioning brake.
- * Spare tire and rim.

STANDARD EQUIPMENT

- * Fabricated from structural channel sections.
- * Steel plate and tubing is used for reinforcement.
- * Undercarriage consists of tandem 20,000 lb. rated axles, with spring suspension.
- * Trailer brakes are straight air ABS system.
- * The unit has one hydraulic front jack and two hydraulic rear stabilizers.
- * Reel lift is accomplished via dual hydraulic cylinders. The reel lift is equipped with individual side frames that traverse hydraulically to align and capture the reel for transport and winding or rewinding.
- * 19 HP water cooled diesel, hydraulic power unit w/keyed ignition, electric start, and 12 gallon fuel tank.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

09-20-2011

TSE International, Inc.
5301 Shreveport-Blanchard Hwy
Shreveport, Louisiana 71107

www.tse-international.com

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853