

CONDUCTOR STRINGING EQUIPMENT **RCSL SRW 21-108X84 SL CABLE REEL WINDER**



STANDARD FEATURES

- * Fully hydrostatic drive system with infinite speed and tension control.
- * Radio Remote Control Console.
- * 66 HP water-cooled diesel engine.
- * 19-gallon fuel tank with level gauge.
- * Cable guidance fairleads.
- * Rear Cable Arm (Snorkel) will trail the main unit two positions.

The Cable Reel Winder is capable of self-loading, winding, paying out and transporting cable reels. The unit is equipped with a closed loop hydraulic system. The reel winder drive system provides for infinitely variable speed controls and allows the cable to be ulled in and tensioned out under controlled tension through the hydraulic system.

PERFORMANCE

Maximum Reel Torque	88,000 lbs. in.
Maximum Reel Speed	16 rpm

REEL CAPACITY

Maximum Reel Diameter	108"
Minimum Reel Diameter	96"
Reel Width	71 - 84"
Arbor Shaft Diameter	5"
Maximum Reel Weight	21,000 lbs.



At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.

09-21-2011

TSE International, Inc.
5301 Shreveport-Blanchard Hwy
Shreveport, Louisiana 71107

Toll Free: 800-825-2402
Telephone: 318-929-2368
FAX: 318-929-4853

www.tse-international.com