

## 6811 TRAILER MOUNTED TAKE-UP REEL WINDER



### STANDARD EQUIPMENT

- Rewinding control from the Puller.
- Provides suitable tail tension to P210 Puller.
- 1,300 lbs. Line Pull at up to 4.5 MPH.
- Independently operate, hydraulically actuated, payout brake to prevent overspin during reel payout.
- Anti-rollback device to prevent accidental payout of the pulling rope during pulling operation.
- Maximum reel capacity: 72 inches diameter x 56 inches wide and 18,000 lbs.
- Tandem axle trailer mounted (suitable for towing speeds up to 65 MPH).
- Air brakes to include ABS systems.
- Four 10R22.5 tires rated @ 5,150 lbs. each.
- Reel shafts to be 3 1/2" in diameter with 24" bronze overspin brake and hydraulically operated caliper.
- Post type levelwind controlled from puller.
- 40,000 lbs. swivel with Allen head screw pin connections.

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.



FM 63723

5301 Shreveport-Blanchard Hwy  
Shreveport, Louisiana 71107



Toll Free: 800.825.2402  
Telephone: 318.929.2368  
FAX: 318.929.4853

[www.tse-international.com](http://www.tse-international.com)