

TSE GRIPS AND SWIVELS

RECOMMENDED SIZING

CONDUCTOR		DIAMETER	CONDUCTOR WEIGHT PER FT.	FLEXIBLE EYE GALVANIZED STEEL	TSE SWIVEL
SIZE	NAME				
2 ACSR	Sparrow	.316	.0091	5601043	SW-9
2 ACSR	Sparate	.325	.1067	5601043	SW-9
1 ACSR	Robin	.355	.1152	5601043	SW-9
1/0 ACSR	Raven	.398	.1452	5601043	SW-9
2/0 ACSR	Quail	.447	.1831	5601043	SW-9
3/0 ACSR	Pigeon	.502	.2309	5601044	SW-13
266.8				5601044	SW-13
4/0 ACSR	Penguin	.563	.2911	5601044	SW-13
336 ACSR	Merlin	.684	.3650	5601044	SW-13
397 ACSR	Chickade	.743	.4310	5601044	SW-13
477 ACSR	Pelican	.814	.5180	5601251	SW-13
556 ACSR	Osprey	.897	.6040	5601251	SW-13
636 ACSR	Kingbird	.940	.6910	5601251	SW-13
636 ACSR	Grosbeak	0.99	.8750	5601251	SW-13
795 ACSR	Coot	1.040	.8050	5601045	SW-14
954 ACSR	Rail	1.165	1.0750	5601045	SW-14
1113 ACSR	Bluejay	1.259	1.2550	P00-9700-029	SW-17
2 AAC	Iris	.292	.0623	5601043	SW-9
1 AAC	Pansey	.328	.0785	5601043	SW-9
1/0 AAC	Poppy	.368	.0991	5601043	SW-9
2/0 AAC	Aster	.414	.1249	5601043	SW-9
3/0 AAC	Phlox	.464	.1575	5601043	SW-9
4/0 AAC	Oxlip	.522	.1986	5601044	SW-13
336.4 AAC	Tulip	.666	.3158	5601044	SW-13
397.5 AAC	Canna	.724	.3732	5601044	SW-13
477 AAC	Cosmos	.793	.4478	5601045	SW-13
556.5 AAC	Dahlia	.856	.5224	5601045	SW-13
636 AAC	Orchid	.918	.5870	5601045	SW-13
795 AAC	Arbutus	1.026	.7463	5601045	SW-14
954 AAC	Magnolia	1.124	.8956	5601045	SW-14
568.3 ACAR	15/4	1.124	.5512	5601251	SW-13
PULLING ROPE:	5/8" Diameter			5601040	SW-13
	3/4" Diameter			5601041	SW-14

At TSE, engineering is a process of continuous product improvement; therefore, specifications are subject to change without notice.



5301 Shreveport-Blanchard Hwy
Shreveport, Louisiana 71107



Toll Free: 800.825.2402
Telephone: 318.929.2368
FAX: 318.929.4853